



## Product Data Sheet

### Product Name: PEELOLINE

**Description:** Highly biodegradable solvent. The main ingredient in PEELOLINE is an extremely safe and non-toxic citrus solvent. This product has a very pleasant and natural citrus odor. This product is used to remove resins, asphalt, dyes, latex, rubber, creosote and many more.

Product Uses & Applications		Application Instructions	
Tank Cleaning		Dilution Rate	Does not dilute with water
Equipment Decontamination		Application Methods	Spray System, 3D Nozzles, Spinner
Line Cleaning		Special Instructions	None.
Substance Removal		<b>Additional Instructions:</b>	
		Allow product to soak into set-up substances for as long as possible. Rinse with warm/hot water to remove product more easily.	
Hazardous Information		Packaging Information	
Specific Hazard	Eye and Skin Irritant!	Available Quantities	5,30, 55, and bulk quantities
Flash Point (°F)	Above 122	Packaging Material	Poly
Biodegradability	Excellent	<b>Other Information:</b>	
pH	N/A for Oils	None.	
Unusual Hazards	Incompatible with plastics		
Other Information	None.		

### Case Study & Application Information

#### September 2, 2008 Chemical Storage Facility N.O., LA

PEELOLINE was used to remove heavy paraffins and tar from an AST. This product was sprayed in through the manways and allowed to soak in for 2 days. High pressure water was used after the 2 days to remove the residues. PEELOLINE did an excellent job in removing the tars. One section of the tank had to be treated again because it was missed with the first treatment. The customer was also happy that there were no odor complaints during the job. PEELOLINE has a pleasant citrus fragrance which masked the hydrocarbon odors during the tank cleaning activities.

#### April 18, 2008 Chemical Facility, Houston, TX

Vapor Tech's PEELOLINE was used to clean out asphalt residues in a tank. Our product was injected by way of spinner and allowed to soak for 1 day. Heat was applied to the tank via steam lines and then the tank was rinsed. Last job required 3 washes to get build-up off walls. Only 2 rinses were required using the PEELOLINE solution.

Visit us on-line at [www.vapor-tech.net](http://www.vapor-tech.net)

Vapor Technologies, Inc. [www.vapor-tech.net](http://www.vapor-tech.net) (409) 316-0173 FAX (281) 754-4876  
7200 Williams Street Hitchcock, TX 77563